

UniFi<sup>®</sup> SWITCH



# UniFi Switch Lite 8 PoE

The USW-Lite-8-PoE is a fully managed Layer 2 switch with eight Gigabit Ethernet ports for your RJ45 Ethernet devices. Four ports also offer auto-sensing 802.3af PoE that provide up to a total PoE wattage of 52W for UniFi Access Points or other PoE devices. Managed and configured by the UniFi Network Controller with UniFi mobile app support, the USW-Lite-8-PoE offers Layer 2 switching protocols and features. The UniFi Network Controller and mobile app allow admins to configure and monitor virtually all of the switch features in a graphical user interface from anywhere.



## Mechanical

|            |  |
|------------|--|
| Dimensions | 99.6 x 163.7 x 31.7 mm (3.92 x 6.44 x 1.25") |
| Weight     | 450 g (15.87 oz)                             |

## Hardware

|                                   |  |
|-----------------------------------|--|
| Total Non-Blocking Line Rate      | 8 Gbps                                       |
| Max. Power Consumption            | 8W   |
| Power Method                      | 54VDC, 1.1A Power Adapter                    |
| Power Supply                      | External 54V/60W Power Adapter               |
| Supported Voltage Range           | DC 50V to 57V                                |
| Networking Interfaces             | (8) 10/100/1000 Mbps Ethernet RJ45 Ports     |
| PoE Interfaces                    | (4) PoE+ IEEE 802.3af/at (Pins 1, 2+; 3, 6-) |
| Management Interface              | Ethernet In-Band                             |
| Max. PoE+ Wattage per Port by PSE | 30W  |
| Modes                             | SMB Layer 2 PoE Gigabit Ethernet Switch      |
| Operating Temperature             | -15 to 40° C (5 to 104° F)                   |
| Operating Humidity                | 10 - 90% Noncondensing                       |
| Certifications                    | CE, FCC, IC                                  |

## LEDs

|          |   |
|----------|---|
| System   | (1) Power, Blue/White<br>Flashing White: Bootup in Progress<br>Flashing Blue: Firmware Upgrading<br>Steady White: Factory Defaults, Awaiting Adoption<br>Steady Blue: Device is Adopted |
| Ethernet | Green: 1G, Amber: 10/100 Mbps   |
| PoE      | Amber: IEEE 802.3af/at  |

