UniFi® Network

UniFi SmartPower 6-Port Power Strip

The UniFi SmartPower Strip is a Wi-Fi connected power strip installed between an AC outlet and the power plugs of your internet connectivity hardware (modems, router, etc). The UniFi Network Controller continuously monitors availability of an internet connection. If the connection drops, the UniFi SmartPower Strip automatically restarts the connected devices by disconnecting power for a short period of time*.

The UniFi SmartPower Strip offers six power control outlets for 125VAC devices (up to 1250W total). Four USB Type C ports can charge smartphones, reading lights, and other devices (up to 1.5A per port).

* Requires UniFi Dream Machine

Mechanical

Dimensions	229.5 x 111.5 x 37.8 mm (9 x 4.4 x 1.5")
Weight	Without Mount: 702 g (1.55 lb) With Wall Mount: 849 g (1.87 lb)
Enclosure Material	Fire Retardant Plastic
Mount Material	Fire Retardant Plastic
Mounting	Magnetic Wall Mount (Kit Included)

Hardware

Processor Specs	ESP8266, 32-bit Tensilica LX106 Core, 160 MHz
Memory Information	4 MB Flash
Management Interface	2.4 GHz Wi-Fi
Networking Interface	802.11 b/g/n Wi-Fi
Power Output	(6) Power Control Outlets,125V, 1250W Max. Total (4) USB Type C Ports, 1.5A Max. per Port, 20W Max. Total
Buttons	(1) Multifunction Button (1) Factory Reset
LEDs	(1) Power, Blue/White Flashing White: Bootup in Progress Flashing Blue: Firmware Upgrading Steady White: Factory Defaults, Awaiting Adoption Steady Blue: Device is Adopted
Max. Power Consumption	1250W for 125VAC
Power Method	AC Input
Power Supply	AC/DC Embedded
Supported Power Voltage	AC Input/Output: 125v~10A Max, 60 Hz
Operating Frequency	2.4 GHz
Antennas	Single-Band Antenna
Max. TX Power	16.9 dBm
MIMO	1x1, 2x1
ESD/EMP Protection	Air/Contact: ± 24 kV
Operating Temperature	0 to 40° C (32 to 104° F)
Operating Humidity	10 - 90% Noncondensing
Certifications	FCC, IC

Software

Wi-Fi Standards	802.11 b/g/n
Power Save	Yes
Wireless Security	WPA2-PSK AES/TKIP

Supported Data Rates (Mbps)

802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n	6.5 - 72.2 Mbps (MCS0 - MCS7, HT 20)